



<b>Max charging power</b>	7,4 kW (1 x 32 A), 22 kW (3 x 32 A) adjustable Type 2 socket (optional shutter) with a cable lock or Type 2 tethered charging cable
<b>Level of protection</b>	IP 56, IK 10
<b>Electrical protection</b>	RCD type A + DC fault current sensors 6 mA (default), RCD Type B or MCB char. C (optional)
<b>User identification</b>	PIN code, RFID, App*
<b>Communication</b>	Ethernet, Wi-Fi or 4G LTE
<b>EV communication</b>	IEC 61851
<b>Connectivity</b>	OCPP 1.6 SOAP & JSON, Modbus TCP
<b>Dynamic Load balancing</b>	Yes
<b>Clustering</b>	Up to 16 chargers, expandable **
<b>Energy meter</b>	Class 2 energy meter, MID optional
<b>Smart building integration (BEM)</b>	Modbus TCP, custom smart meter integration
<b>User interfaces</b>	LCD Screen, embedded web interface My INCH, App*
<b>Demand response capabilities</b>	Frequency control, digital inputs 12V DC signal optional, OCPP
<b>Material</b>	Aluminium housing, Polycarbonate Lexan cover plate
<b>Colour options</b>	Graphite Grey, White optional

\*\*Depending on characteristics of charging site.

\*When connected to a charge point management system.



# OUTSTANDING USER EXPERIENCE IN HARMONY WITH THE GRID.

Etrel INCH Pro chargers enable charge point operators to serve a large number of EVs, even in locations with limited power supply. Etrel INCH works with two priorities in mind – to enable the best user experience and reduce operating costs, dynamically balancing charging power for more energy-efficient charging.

INCH can remember and predict known users' charging habits by creating charging profiles from use patterns and energy tariffs, ensuring a smooth and cost-efficient charging experience. Unique magnetic cable holder allows EV drivers to handle and store the charging cable faster. A touch LCD screen, indicator light and sounds enable the user to adopt a preferred method of charger interaction for immediate convenience.

Advanced load management algorithms ensure safe installation on almost any location without costly grid connection point upgrades. Coupled with the Load Guard sensor or connected to the building energy management system, chargers utilise dynamic load management algorithms to adjust charging power to other buildings' consumers and prevent overloads.

When connected in a cluster with limited available charging power, the power is distributed intelligently among all chargers, based on EV characteristics and priorities.

The durable enclosure of INCH Pro charging station is built to withstand the harshest weather conditions while allowing the business to stand out with the design.

## Large Cluster Solution

Local load management ensures stable operation regardless of an external connection. Etrel Large Cluster Solution INCH chargers seamlessly operate in large installations, such as residential buildings or fleet car parks within the grid connection point limitation.

## Refurbishment

We are helping our partners keep their assets up-to-date and at top performance by taking used Etrel chargers, making them up-to-date, substantially extending their lifespan and reducing their environmental impact.

