

PLUG CHARGER GO

Technical specifications

Maximum charging power	30	[kW]
Input		
Power supply [V / Hz]	AC, 3x400 / 50	
Connection power [kVA]	33	
Connection to mains	CEE 63A socket 3P+N+PE	
Power factor	> 0,98	
Output		
Efficiency [%]	> 94	
Maximum charging current [A]	100	
Output voltage range [V]	150 - 1000	
Communication		
Charging mode	IEC 61851-1 IEC 61851-23 IEC 61851-24 ISO 15118 DIN 70121	
Protocol	OCPP 1.6-J OCPP 2.0.1	
General		
Housing	Aluminium	
Protection rating	IP 54 IK 10 IK8 - Touchscreen	
Overall dimensions [H x W x D]	1000 x 630 x 450	
Weight [Kg]	~ 50	
Noise [dBA]	< 60	
Operating temperature range [°C]	- 25 - +55 > 40 possible output power limitation	
Operating altitude [m.a.s.l.]	≤ 2000	
Compliance with standards	CE LVD 2014/35/UE EMC 2014/30/UE RED 2014/53/UE	

PLUG CHARGER GO

Equipment

Maximum charging power	30	[kW]
Connectors		
DC Connectors	CCS 4m	
Housing		
Colour RAL 9016	✓	
RAL Colour (Other)	Option	
Additional branding	Option	
Anti-graffiti	Option	
Interface		
Display	7" Touchscreen display with integrated RFID card reader	
Power switch Option	Adjustable output power of 1kW	
Emergency button	✓	
Meters		
Output energy meter	✓	
Communication		
Data transfer	GSM (LTE) EEP GSM (LTE) Client	
	Ethernet Option	
Catalog code	PCG -A210B0000K -9016	